

Leisure Time Liquid Spa Down

1. Product And Company Identification]
Supplier Leisure Time 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com	Manufacturer Advantis Technologies, Inc. 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com			
Supplier Emergency Contacts & Phone Number CHEMTREC - DAY OR NIGHT: (800) 424-9300	Manufacturer Emergency Contacts & Phone Number CHEMTREC - DAY OR NIGHT: (800) 424-9300			
Issue Date: 03/10/2006 Product Name: Leisure Time Liquid Spa Down Chemical Name: Sodium bisulfate CAS Number: Not Established Chemical Family: pH reducer Chemical Formula: Proprietary Mixture MSDS Number: 43				
2. Composition/Information On Ingredients				
Ingredient Name		CAS Number		Percent Of TotalWeight
SODIUMBISULFATE 7681-38-1 Ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200. Materials determined to be health hazards are listed if they comprise 1% or more of the composition. Materials identified as carcinogens are listed if they comprise 0.1% or more of the composition. Information on proprietary materials is available in 29CFR 1910.1200(i)(1).				
Hazards Identification (Pictograms)				
Skin Contact Eye Hazards Causes eye irritation. Skin Hazards Causes skin irritation. Ingestion Hazards				
Harmful if swallowed. <u>Inhalation Hazards</u> Causes respiratory tract irritation.				

Leisure Time Liquid Spa Down

3. Hazards Identification - Continued Signs And Symptoms Irritation of Eyes, Skin and Respiratory Passages First Aid (Pictograms) 4. First Aid Measures Eye In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Call a physician or a poison control center immediately. Skin In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Ingestion DO NOT INDUCE VOMITING. Call a physician or a poison control center immediately. If victim is fully conscious, give one or two cups of water or milk to drink. Inhalation If breathing is difficult, give oxygen. If inhaled, remove to fresh air. Fire Fighting (Pictograms)

5. Fire Fighting Measures

Flash Point: N/A °F Flammability Class: N/A

Fire And Explosion Hazards

At temperatures in excess of 570 F, hazardous fumes of sulfur dioxide and sulfur trioxide are evolved. Use forced draft ventilation or gas mask.

Extinguishing Media

Use the appropriate extinguishing media for the surrounding fire.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear. Water can be used to cool and protect exposed material.

6. Accidental Release Measures

Clean up spill immediately. Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Neutralize spill area with soda ash or lime. Flush spill area with water. Use appropriate containers to avoid environmental contamination.

Leisure Time Liquid Spa Down

Handling & Storage (Pictograms)



7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store material in a cool and dry place. Keep containers tightly closed.

Handling Precautions

Use only with adequate personal protection.

Storage Precautions

Store in a cool dry place.

Work/Hygienic Practices

Use safe chemical handling procedures suitable for the hazards presended by this material. Avoid contact with eyes. Solutions of this material are acidic and strongly irritating. Will attack most metals.

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls

Local exhaust acceptable. Special exhaust not required

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Chemical-resistant gloves.

Respiratory Protection

None normally required.

9. Physical And Chemical Properties

Appearance

Pink liquid

<u>Odor</u>

Slightly Acidic

Chemical Type: Mixture Physical State: Liquid Melting Point: n/a °F Boiling Point: 220 °F Specific Gravity: 1.30 Molecular Weight: NOT DETERMINED Percent Volitales: NOT DETERMINED Vapor Pressure: NOT DETERMINED pH Factor: <1 Solubility: SOLUBLE

Leisure Time Liquid Spa Down

10. Stability And Reactivity				
Stability: Stable				
Hazardous Polymerization: Will not occur.				
Hazardous Decomposition Products At Temperatures in excess of 570F Hazardous fumes of Sulfer Dioxide and Sulfer Trioxide are evolved.				
11. Toxicological Information				
<u>Acute Oral Effects</u> LD50 Rat: >5g/kg				
12. Ecological Information				
No Data Available				
13. Disposal Considerations				
Dispose in accordance with applicable federal, state and local government regulations.				
14. Transport Information				
Proper Shipping Name Bisulfate, Aqueous Solution				
<u>Hazard Class</u> 8, PGII (<1L Consumer Commodity ORM-D)				
DOT Identification Number UN2837				
15. Regulatory Information				
Ingredient(s) - State Regulations SODIUM BISULFATE New Jersey - Workplace Hazard New Jersey - Special Hazard New York City - Hazardous Substance				
Canadian Regulatory Information Class E - Corrosive Material Class D, Div 2b- Poisonous or Infectious Material: other toxic effects				
NFPA HMIS				
HEALTH 3				
FLAMMABILITY 0				
PERSONAL PROTECTION C				
16. Other Information				
Revision/Preparer Information				
MSDS Preparer: jw3 This MSDS Superceeds A Previous MSDS Dated: 07/26/2000				
Disclaimer				
No Data Available				

Leisure Time Liquid Spa Down

Disclaimer - Continued

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Leisure Time

Printed Using MSDS Generator[™] 2000